

POWER, PERFORMANCE & PRECISION

160,000 lbs. maximum capacity [72,500 kgs.]



- · Orion's quick-change attachment systems
- Durable components, long dependable life.
- · Smooth, controlled hydrostatic drive
- · Powerful V8, LP power
- Made in Canada



orionlifts.com



Component Weights:

Chassis w/forks & all ctwts: 125,000 lbs. Forks/carriage: 10,100 lbs.

Front: 38,960 lbs. Boom: 15,360 lbs. Rear: 86,040 lbs. Boom & Stand: 17,288 lbs.


Chassis w/forks & w/o ctwts: 65,000 lbs.

Counterweights: 6,000lbs. x 10

Front: 38,960 lbs. Counterweights: 6,000 lbs.

Rear: 26,040 lbs.

Boom Specifications



Rated Boom Capacities (lbs.)											
LC in Inches >	12"	24"	36"	48"	60"	72"	84"	96"	108"	120"	132"
0 CWT	48,710	40,970	35,350	31,090	27,740	25,040	22,830	20,970	19,390	18,030	16,860
2 CWT	72,490	60,970	52,610	46,260	41,280	37,270	33,970	31,210	28,860	26,840	25,080
4 CWT	96,270	80,970	69,860	61,440	54,820	49,500	45,110	41,440	38,330	35,640	33,310
6 CWT	120,050	100,970	87,120	76,610	68,370	61,720	56,260	51,680	47,790	44,450	41,540
8 CWT	140,000	120,970	104,380	91,790	81,910	73,950	67,400	61,920	57,260	53,250	49,770
10 CWT	155,000	130,000	111,000	95,000	84,000	75,000	67,400	61,920	57,260	53,250	49,770

*CAPACITIES RATED WITH MAST VERTICAL



160,000 lbs. @ 24" w/Sideshift

115,000 lbs. @ 48" w/Sideshift

Lift Height (clear): 132" Overall Width: 102"

Free Lift: 50" Overall Length: 230" Standard Forks dimensions: 96" x 12" x 6" Wheelbase: 150"

Max distance between standard forks: 71" Engine/Fuel: 5.7L V-8 GM LP Industrial

Max distance outside-to-outside forks: 95" Hydrostatic Pump: Danfoss

Min distance between forks: 5" Gradability: 20% Loaded, 60% Unloaded

Max lift height w/boom: 32'


Max horizontal reach w/boom: 132"

Tires Front: 48" x 30" non-marking

Tires Rear: 45" x 12" non-marking

Travel Height: 136"

Forklift Specifications



Rated Fork Capacities (lbs.)											
LC in Inches >	24"	36"	48"	60"	72"	84"	96"				
0 CWT	49,770	42,010	36,350	32,030	28,630	25,880	23,610				
2 CWT	72,850	61,490	53,200	46,880	41,900	37,880	34,560				
4 CWT	95,920	80,970	70,060	61,730	55,180	49,880	45,510				
6 CWT	119,000	100,450	86,910	76,580	68,450	61,880	56,460				
8 CWT	142,080	119,940	103,760	91,340	81,730	73,940	67,510				
10 CWT	160,000	133,000	115,000	103,000	81,730	73,940	67,510				

*CAPACITIES RATED WITH MAST VERTICAL



POWER, PERFORMANCE & PRECISION

ORION 160K features:

- ✓ The Orion Quick Change Riggers' Boom is safer and faster to install AND it improves boom lifting capacities.
- Full-power fork locators align the forks where you need them, when you need them, effortlessly.
- Tilt and roll angle sensors: Continuously monitor equipment orientation, ensuring safe operations and precise positioning every time.
- ✓ Easy-Read Electronic Load Scale: Instantly gauge the weight of your cargo with crystal-clear accuracy, ensuring safe and efficient operations every time.
- Rugged design and durable construction: Built to last with long-life components, ensuring consistent performance and reliability throughout its lifespan.



Back up camera, back up alarm, among the safety features standard.



Very Low Lift LP Tank Loading. Improves safety immensely.

Optional Equipment:

- ✓ Variety in forks: Whether you need coil prong, coil forks, extra long forks, or another type, select the perfect fit for the task at hand, enhancing load versatility.
- ✓ Extra-wide/side-shifting custom carriages ensure precision in load placement and adaptability for diverse operations.
- ✓ Diesel Power offers consistent performance and reliable, long-lasting operation.
- Operator's cab equipped with heating and AC: Stay comfortable and focused in any climate, ensuring efficient operations.
- ✓ Full-function Digital Radio Remote Control: Effortlessly steer, drive, and lift with unparalleled precision and from a safe distance.
- ✓ Front & backup cameras: Navigate with confidence, enhancing safety and minimizing risks in both forward and reverse directions.



Easy-to-Use power fork locators for supporting different sized loads.



State-of-the-art electronic easy-read load scale.



